
SS4083

8.3 kWh Advanced LiFePO4 Battery



5 Years
Guarantee on Product Material & Workmanship

10 Years
Energy Output Warranty

Tesla Solar SA

Our SS4083 lithium iron phosphate battery system boasts a modular design which can be wall or floor mounted. You can easily scale its capacity by connecting multiple units in parallel, making it ideal for various applications.

Features

- **High efficiency**
- **High energy density**
- **Long life cycle**
- **Stable discharge platform**
- **Green technology**
- **High temperature performance**
- **Excellent safety**
- **High charge & discharge rate**


Applications

- Off-Grid Systems
- Hybrid Systems
- Grid Tied Systems
- Charger Systems
- Residential UPS Systems
- Commercial UPS Systems



SS4083	
Cell Chemistry	Lithium Iron Phosphate (LiFePO4)
Cell Manufacturer	CALB
Rated Capacity	8.3 kWh
Nominal Power @0.7C	7.5 kW
Nominal Voltage	51.2V
Operational Voltage	44.8 - 55.6Vdc
Max Charge & Discharge Current	150A
Cycle Life @25°C	≥4000
Charging Efficiency	99%
Operational Temperature	0°C to 50°C
Communication	CANBUS / RS485
Weight per module	70kg
Dimensions (W x D x H)	389mm x 186mm x 631mm
Storage Duration	6 months @25°C
Safety Standard Compliance	CE / EN 55016 / IEC 61000
Cell Certificate	IEC 62619 / UN38.3 / UN3480 / UL 1642 / UL 1973

Battery Management System




Each Solar MD battery has its own Battery Management System (BMS) designed and built in-house. The BMS handles the internal functions of each battery. In setups with multiple batteries, the BMS independently manages each one, ensuring a stable energy flow throughout the battery system.

- **Data collection & storage for monitoring**
- **Efficient charging & discharging control**
- **Precise cell voltage measurement**
- **Built in temperature sensors & external sensor inputs**
- **Voltage management to prevent damage**
- **Cell balancing for extended lifespan**
- **SOC Calculation & Control**
- **CANBUS & RS485 Communication**
- **CE / IEC61000**
- **2x Programmable Isolated Outputs**

Monitoring & Control

The EMS integrates seamlessly with various brands and devices, including energy meters, generators, chargers, and inverters. This capability enables real-time adjustments to energy consumption and production, empowering you to make informed decisions for optimal system management. Regular reports provide insights into energy consumption, cost savings, and environmental impact.





Logger V2 (The Device)

The High-Performance Logger V2 offers easy and fast communication with automatic device discovery and connection.

- **Interfaces** include CAN Bus, RS232, RS485, Ethernet, and Wi-Fi (client and station).
- Integrated **programmable relays,** digital inputs, digital outputs, analogue input, analogue output for load control.
- **Communicates with** supported inverters, energy meters, weather stations, and other energy devices.

mypower24 (The Platform)

mypower24 is a comprehensive management platform designed to simplify and centralise the control of your energy devices. Seamlessly integrating with your Logger V2, mypower24 offers a robust suite of features that effectively manage and optimise your energy infrastructure:

- **Real-Time Data & Insights:** Gain valuable insights into your energy usage with real-time data visualisation and historical records.
- **Safe & Secure:** High-security standards via certified authentication and encrypted data transfer.
- **Convenient Remote Management:** Remotely manage your system & devices for maximum efficiency.

STUDER SMA mlt INVERTERS Deye MICROCARE SOLAR ENERGY victron energy Voltronic Power SOFAR
SUN SYNK SUNGROW Clean power for all GOODWE SERMATEC solis ABB HUAWEI
Tesla Solar SA

Contact Us


021 555 2181


076 280 4053


Info@solarmd.co.za


solarmd.com

Tesla Solar SA